Amendments to the Claims:

10/537119 JC17 Rec'd PCT/PTO 03 JUN 2005

The following listing of claims will replace all prior versions, and listings, of claims in the application:

- 1. (Original) A two-dimensional photonic crystal slab having a three-dimensional local structure, characterized by that it comprises:
 - a) a slab-shaped body;
- b) a plurality of areas having a refractive index different from that of the body, which are periodically arranged in the body; and
 - c) a refractive index member mounted on the surface of the body.
- 2. (Original) The two-dimensional photonic crystal slab having a three-dimensional local structure according to claim 1, characterized in that it comprises a waveguide formed by providing a linear defect of the modified refractive index areas in proximity to the refractive index member.
- 3. (Currently Amended) The two-dimensional photonic crystal slab having a three-dimensional local structure according to claim 1-or-2, characterized in that two or more pieces of the refractive index members differing in material, shape or size are mounted on the body.
- 4. (Currently Amended) The two-dimensional photonic crystal slab having a three-dimensional local structure according to one of claims 1-3 claim 1, characterized in that a point-like defect of the modified refractive index areas are provided within the body and a refractive index member is additionally mounted at the position of the point-like defect.

- 5. (Original) The two-dimensional photonic crystal slab having a three-dimensional local structure according to claim 4, characterized in that a plurality of point-like defects of the modified refractive index areas having different resonant wavelengths are provided within the body, and a plurality of the refractive index members identical in material, shape and size are arranged on a surface of the body at positions of the point-like defects.
- 6. (Currently Amended) The two-dimensional photonic crystal slab having a three-dimensional local structure according to one of claims 1-5 claim 1, characterized in that the refractive index members are mounted on both sides of the body.
- 7. (Original) The two-dimensional photonic crystal slab having a three-dimensional local structure according to claim 6, characterized in that the refractive index members are mounted at the same position on both sides of the body.
- 8. (Original) The two-dimensional photonic crystal slab having a three-dimensional local structure according to claim 7, characterized in that identical refractive index members are mounted at the same position on both sides of the body.
- 9. (Currently Amended) The two-dimensional photonic crystal slab having a three-dimensional local structure according to one of claims 1-8 claim 1, characterized in that it is provided with a point-like defect of the modified index areas asymmetrical between front and back sides.

- 10. (Currently Amended) The two-dimensional photonic crystal slab having a three-dimensional local structure according to one of claims 1-9 claim 1, characterized in that the refractive index member is made of the same material as that of the body.
- 11. (Currently Amended) The two-dimensional photonic crystal slab having a three-dimensional local structure according to one of claims 1-9 claim 1, characterized in that the refractive index member is made of a material whose refractive index changes when the material receives an external operation.
- 12. (Currently Amended) The two-dimensional photonic crystal slab having a three-dimensional local structure according to one of claims 1-11 claim 1, characterized in that the refractive index member is a cylinder whose top is concave or convex.
- 13. (Original) A method of manufacturing a two-dimensional photonic crystal slab having a three-dimensional local structure, characterized by that it comprises a process for creating a refractive index member in which a gas material used for creating a refractive index member is introduced onto a two-dimensional photonic crystal and a focused ion beam is irradiated onto the crystal to deposit the refractive index member.
- 14. (Original) A method of manufacturing a two-dimensional photonic crystal slab having a three-dimensional local structure, characterized by that it comprises a process for creating a refractive index member in which a refractive index member beforehand is mounted onto the two-dimensional photonic crystal with a nanomanipulator.